



# MATERIAL SAFETY DATA SHEET

## AHD Fade Away

Issue date: 15/6/2020

### **SECTION 1: SUBSTANCE IDENTIFICATION AND SUPPLIER**

Product name: AHD Fade Away

Recommended Use: A scourable spray-on dye for marking sheep / livestock

Company identification Address:

1229 Maraekakaho Road  
Hastings 4175  
New Zealand  
Phone (06) 873 3611

Poisons Information Centre: 0800-764-766

Or CHEMCAL 0800-243-622 24hr emergencies only

Transport Emergency 111 Fire and police

### **SECTION 2: HAZARD IDENTIFICATION**

2.1 Classified as a Dangerous Good according to NZS 5433:2007

Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2017

Subclasses: 2.1.2 Category A – Flammable Aerosols.

Subclass 6.1 Category E – Substances which are acutely toxic.

Subclass 6.3 Category B – Substances that are mildly irritating to the skin.

Subclass 9.1 Category B – Substances that are ecotoxic in the aquatic environment.

#### **2.2 Hazard and Precautionary Information:**

**Warning.** Flammable aerosol. Causes mild skin irritation. May be harmful if inhaled. Toxic to aquatic life with long lasting effects. Keep out of reach of children. Read label before use. Read Safety Data Sheet before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C.



#### 2.3 Risk Phrase(s):

R12 Extremely Flammable.

R36 Irritating to eyes.

R38 Irritating to skin.

R44 Risk of explosion if heated under confinement.

R67 Vapors may cause drowsiness and dizziness.

#### 2.4 Safety Phrase(s)

S16 Keep away from sources of ignition - No smoking.

S23 Do not breathe gas/fumes/vapor/spray.

S26 In case of contact with eyes, rinse immediately with plenty of water & seek medical advice.

S33 Take precautionary measures against static discharges.

S35 This material and its container must be disposed of in a safe way.

S36/37 Wear suitable protective clothing and gloves.

S61 Avoid release to the environment. Refer to special instructions/safety data sheet.  
S9 Keep container in a well-ventilated place.

### **SECTION 3: COMPOSITION INFORMATION**

<b>INGREDIENT</b>	<b>CAS Number.</b>	<b>Proportion</b>
Aliphatic hydrocarbon (heptanes)	64742-49-0	30-60%
Butane	106-97-8	10-<30%
Propane	74-98-6	10-<30%
Acetone	67-64-1	<10%
Isopropanol	67-63-0	<10%
Non-Hazardous	N/A	To 100%

### **SECTION 4: FIRST AID MEASURES**

For advice, contact a Poisons Information Centre (Phone New Zealand 0 800 764766) or a doctor.

- 4.1 **Inhalation:** Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.
- 4.3 **Skin Contact:** If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice
- 4.4 **Eye Contact:** If in eyes, wash out immediately with water. In all cases of eye contamination, it is a sensible precaution to seek medical advice.
- 4.5 **Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.
- 4.6 **Medical attention and special treatment:** Treat symptomatically.

### **SECTION 5: FIRE FIGHTING MEASURES**

- 5.1 **Hazardous Combustion Products:** Flammable gas. On burning will emit toxic fumes, including those of oxides of carbon
- 5.2 **Precautions for fire fighters and special protective equipment:** Heating can cause expansion or decomposition of the material, which can lead to the containers exploding. If safe to do so, remove containers from the path of fire. Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapor or products of combustion.
- 5.3 **Suitable extinguishing media:** Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).
- 5.4 **HAZCHEM Code:** 2YE

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

- 6.1 **Emergency procedures:** Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).
- 6.2 **Methods and materials for containment and clean up:** In the event of an aerosol can developing a leak, allow to fully discharge in the open air before disposal.

**SECTION: 7 HANDLING AND STORAGE**

- 7.1 **Precautions for safe handling:** Avoid skin and eye contact and breathing in vapor, mists and aerosols. Ensure spray nozzle is always directed away from the user. May form flammable vapor mixtures with air. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke. Vapor may travel a considerable distance to source of ignition and flash back
- 7.2 **Conditions for safe storage:** Store in cool place and out of direct sunlight. Store away from sources of heat or ignition. Store away from oxidising agents. Keep containers closed when not in use - check regularly for leaks.

**SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION**

- 8.1 **Occupational Exposure Limits:** No value assigned for this specific material by the New Zealand Occupational Safety and Health Service (OSH). However, Workplace Exposure Standard(s) for constituent(s):
- Butane: WES-TWA 800 ppm, 1,900 mg/m<sup>3</sup>  
 Propane: Simple asphyxiant-may present an explosion hazard  
 Exxsol DSP80/100: WES-TWA 244 ppm, 1000 mg/m<sup>3</sup>

As published by the New Zealand Occupational Safety and Health Service (OSH).

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure. Asphyxiant - gases which can lead to reduction of oxygen concentration by displacement or dilution. The minimum oxygen content in air should be 18% by volume under normal atmospheric pressure. These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

- 8.2 **Engineering Controls:** Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Use in well ventilated areas. Keep containers closed when not in use. An asphyxiant gas which can lead to the displacement or dilution of oxygen. The minimum oxygen content in air should be 18% by volume under normal atmospheric pressure.
- 8.4 **Personal Protective Equipment:** The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors. Wear clean overalls, safety boots, general purpose gloves (PVC) and safety spectacles. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. For leaking aerosol cans: Wear clean overalls, safety boots, general purpose gloves (PVC) and full face visor. If risk of inhalation exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.
- 8.5 **FOR CONSUMER USE:** Wear rubber gloves and eye protection while handling the product. Wash hands after use.

**SECTION 9: PHYSICAL DESCRIPTION / PROPERTIES**

Physical state:	Aerosol
Odour:	Hydrocarbon
Solubility:	Insoluble in Wter
Specific Gravity:	0.70@20°C
Relative vapor density (air=1):	>1
Vapor pressure (20°C):	N Av

Flash point (°C):	<0 (Hydrocarbon propellant)
Flammability Limits (%):	N Av
Can pressure:	<8 bar
Auto ignition Temperature (°c)	N Av

## **SECTION 10: STABILITY AND REACTIVITY**

- 10.1 Chemical stability: Stable under normal conditions of use.
- 10.2 Conditions to avoid: Avoid exposure to heat, sources of ignition, and open flame.
- 10.3 Incompatible materials: Incompatible with oxidising agents.
- 10.4 Hazardous decomposition products: Oxides of carbon.
- 10.5 Hazardous reactions: Hazardous polymerisation will not occur.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

**Ingestion:** Swallowing can result in nausea, vomiting and central nervous system depression. If The victim is showing signs of central system depression (like those of drunkenness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs. Breathing in vomit may lead to aspiration pneumonia (inflammation of the lung).

**Eye contact:** May be an eye irritant.

**Skin contact:** Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis.

**Inhalation:** Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness. Intentional misuse by deliberately concentrating and breathing the contents can be harmful or fatal.

**Long Term Effects:** No information available for the product.

**Toxicological Data:** No LD50 data available for the product.

## **SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicity Avoid contaminating waterways.

## **SECTION 13: DISPOSAL INFORMATION**

Disposal methods: Refer to Waste Management Authority. Advise flammable nature. Do not puncture or burn can when empty; contents are under pressure. If aerosol can develops a leak, allow to fully discharge before disposal. Normally suitable for disposal at approved land waste site.

**SECTION 14: TRANSPORT INFORMATION**

- 14.1 **Road and Rail Transport:** Classified as a Dangerous Good according to NZS 5433:2007 Transport of Dangerous Goods on Land.  
UN No: 1950  
**Class-primary:** 2.1 Flammable Gas  
**Proper Shipping Name:** AEROSOLS  
**Hazchem Code:** 2YE
- 14.2 **Marine Transport:** Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.  
**UN No:** 1950  
**Class-primary 2.1** Flammable Gas  
**Proper Shipping Name:** AEROSOLS
- 14.3 **Air Transport:** Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.  
UN No: 1950  
**Class-primary:** 2.1 Flammable Gas  
**Proper Shipping Name:** AEROSOLS, FLAMMABLE

**SECTION 15: REGULATORY INFORMATION**

Regulatory information specific for the substance or mixture  
This substance is to be managed using the conditions specified in an applicable Group Standard  
HSR Number: HSR002515 Aerosols (Flammable) Group Standard 2017.

**SECTION 16: OTHER INFORMATION**

For further copies of this sheet or other product information contact AHD LTD. Reason(s) for Issue: Revised Primary SDS  
Change to Poisons Requirements  
This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since AHD Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material. If clarification or further information is needed, the user should contact their AHD representative or AHD Ltd at the contact details on page 1. AHD Ltd responsibility for the material as sold is subject to the terms and conditions of sale.

***DISCLAIMER***

*The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material. The information is provided in good faith based on current knowledge and experience. No warranty with regard to the product properties is expressed or implied.*